

Lithium-ion battery 230 kWh

Lithium-ion battery 230 kWh

The MG LFP Battery 24 V is available in three versions: LFP 230, LFP 304 and the LFP 304 SLP. The third generation LiFePO₄ chemistry forms the basis of this safe and reliable battery. This battery is fully scalable in both voltage and capacity. Easily expand your energy storage system (ESS) by connecting the LFP batteries in parallel and series. Connect up to 16 modules in series, to create a system voltage of 470 Vdc. And with the 304 SLP battery you can connect up to 22 in series to create a system voltage of 563 Vdc. Adding more parallel strings increases the system capacity. As a result, you can reach system capacities of over 1 MWh.

The MG LFP Battery 24 V is available in three versions: LFP 230, LFP 304 and the LFP 304 SLP. The third generation LiFePO₄ chemistry forms the basis of this safe and reliable battery. This battery is fully scalable in both voltage and capacity. Easily expand your energy storage system (ESS) by connecting the LFP batteries in parallel and series. Connect up to 16 modules in series, to create a battery voltage of 470 Vdc. Adding more parallel strings increases the system capacity. As a result, you can reach system capacities of over 1 MWh.

Route the cabling over the batteries by using the cable trays. This prevents cable tangling. Through the innovative design, MG battery systems ensure a neat system installation. The LFP 304 SLP is equipped with front side connectors for cabling.

The CAN-Bus enables communication between the LFP Battery and the MG Master BMS. The MG Master collects and monitors all relevant data from the entire battery bank. The LFP batteries 24 V are available with RJ45 or M12 CAN-Bus connectors.

LFP 24 V battery modules comply with several standards. ES-Trin regulations IEC-EN 62619 & IEC-EN 62620 for the LFP 280, LFP 304 and LFP 304 SLP are approved. The LFP 230 is IEC-EN 62620 approved and IEC-EN 62619 is in progress.

In addition, the battery modules are tested following the UN38.3 transportation tests for lithium-ion batteries. These standards include safety and performance tests on both cell and module level including the battery management system. This includes thermal tests, altitude simulation, vibration, shock, overcharge and external short-circuit.

To ensure a neat installation, use the modular rack system for the LFP series. The LFP 304 SLP batteries racks are specially designed with a slide-in mechanism, in such a way that only front access is needed. As a result, the installation is easy and front-side-only. The rack can be configured in different dimensions. It is offered as a kit, which makes it suitable for use in existing spaces in any application. In other words, minimal integration engineering is required.



Lithium-ion battery 230 kWh

Modular design Offered as a kit Module slide-in Easy front-only installation

By putting the LiFePO₄ batteries in series, you can easily scale the voltage level. For example, four batteries in series creates a system voltage of 96 Vdc. As a result the LFP battery 24 V is an excellent choice for many applications. For instance: electric propulsion, mobile power packs and generator replacement. In addition, they are often used for solar energy storage and peak shaving purposes. Every MG energy storage system must include an MG Master battery management controller for safe and reliable operation. Connect multiple MG Masters in parallel to create larger systems up to 1 MWh. The optional SmartLink MX provides the possibility to create redundant systems. This increases the reliability of your battery system even more.

This model is equipped with Amphenol SurLok Plus connectors. With this additional model, MG takes the famous LFP 304 battery to a higher level in terms of safety and ease of installation. This SLP version is compatible with both the MG Master LV and MG Master HV They are the best choice within the LFP Series for all high-voltage applications in combination with our MG Master HV (BMS).

Besides improved safety and easier installation, another benefit of the new SurLok connectors is that the maximum voltage has been increased. The normal LFP 230 and LFP 304 versions were limited to a maximum of 16 LFP batteries in series (nominal 409 Vdc). With the LFP 304 SLP, the number of batteries in series increased to a maximum of 22 batteries in series. This results in battery bank configurations with a nominal voltage of 563 Vdc.

By putting the LiFePO₄ batteries in series, you can easily scale the voltage level. For example, four batteries in series creates a system voltage of 96 Vdc. As a result the LFP 24 V battery is an excellent choice for many applications. For instance: electric propulsion, mobile power packs and generator replacement. In addition, they are often used for solar energy storage and peak shaving purposes. Every MG energy storage system must include an MG Master battery management controller for safe and reliable operation. Connect multiple MG Masters in parallel to create larger systems up to 1 MWh. The optional SmartLink MX provides the possibility to create redundant systems. This increases the reliability of your battery system even more.

Contact us for free full report

Web: <https://www.kary.com.pl/contact-us/>

Email: energystorage2000@gmail.com

WhatsApp: 8613816583346

